

## Altas Go PT

### 2K 4G LTE 360° PT Battery/ Solar Security Camera

- 10s Pre-recording
- 6-Month Battery Life
- ColorX Night Vision
- Pan, Tilt & Auto-Tracking

## Specifications

Video & Audio	
Image Sensor	1/1.8" CMOS sensor
Resolution	2560×1440 (4 megapixels) @15fps
Lens	f=4mm, F1.0
Video Compression	H.264/H.265
Field of View	Diagonal: 108° Horizontal: 104° Vertical: 54°
Infrared Night Vision	10m (33 ft); 3pcs/1.4W/940nm
Color Night Vision	3pcs/1.4W/6500K
Frame Rate	Main/Sub stream: 10fps-15fps (default: 15fps)
Audio	Two-way audio
Battery	
Battery Capacity	3.6V 20000mAh rechargeable battery (battery life varies based on settings, usage & temperature)
Power Requirements	
Power Capacity	66Wh

<b>Power</b>	
Solar	Reolink Solar Panel 2 (6W); Reolink Solar Panel 3 (12W)
<b>Interface</b>	
Power Port	USB Type-C port (supporting USB-A to USB-C cable only)
microSD Card Slot	Supports max. 512GB microSD card
Reset Button	YES
Audio In/Out	Built-in microphone and speaker
<b>Pan &amp; Tilt</b>	
PT Angle(Max.)	Pan: 355°; Tilt: 90°
Auto Tracking	YES
<b>3G/4G</b>	
LTE Module	<ul style="list-style-type: none"> <li>• Europe: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8</li> <li>• America: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71</li> <li>• Australia: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8</li> </ul>
<b>Software</b>	
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)
<b>Feature Highlights</b>	
Pre-recording	2-10s pre-recording, 10s & 3fps by default, 1/3/5fps adjustable
<b>Other Features</b>	
Smart Alarm	PIR detection, person detection, vehicle detection, animal detection
PIR Detecting Distance	Adjustable, up to 10m (33ft)
PIR Detecting Angle	110° horizontal
Recording Modes	

	Motion-triggered recording, scheduled recording, continuous recording
Time Lapse	YES
Smart Home Compatibility	Google Assistant
Home Hub Compatibility	No
Cloud Storage	Supports Reolink Cloud (available in selected countries)
<b>Working Environment</b>	
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Operating Humidity	20%–85%
Weatherproof	IP65
<b>Mechanical</b>	
Dimensions	178×151×102mm
Weight	875g
<b>Warranty</b>	
Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> .

## Gallery & Specs



1. Antenna
2. Mount
3. Spotlight
4. Lens
5. PIR Sensor
6. CDS
7. Mic
8. Indicator Light



1. Power Button

2. Type-C Port

3. Speaker

4. SIM Card Slot

5. microSD Card Slot