



Product info sheet

Version 1 / 13.01.25

ABSINA TYPE 2 SCHUKO CHARGER

MODE 2 | 6-16A | MAX. 3.7KW | 230V

The adjustable type 2 Schuko charging cable is designed for mobile use at standard household 230V sockets. The charging current can be easily adjusted from 1.4kW to 3.7kW. The durable cable with charging control box can be used on all standard electric and hybrid vehicles with a type 2 or CCS2 plug and is supplied in a high-quality hard case.

PRODUCT HIGHLIGHTS

- Adjustable charging power 6A / 8A / 10A / 13A / 16A - max. 3.7kW, 1-phase, charging control box and protection class IP67 for mobile charging at standard household 230V sockets.
- Safe charging with built-in temperature sensor and type A+DC 6mA residual current circuit breaker. Compatible with all electric cars (BEV) & plug-in hybrids (PHEV) with a type 2 or CCS2 plug according to EU standard IEC 62196-2.
- Type 2 plugs with impact-resistant housing, drive-over protection up to 2 tons and 10,000 mating cycles enable daily use for over 10 years.
- Convenient charging thanks to the 6.0 meter cable length and robust multifunctional Velcro strap with hanging loop for storing or hanging up the charging cable.
- Robust hard-shell case made from recycled plastic with a snap hook on the side and space for up to two charging cables and accessories.

TECHNICAL INFORMATION

Charging capacity: 1.4-1.8-2.3-3.0-3.7kW

Output current: 6-8-10-13-16A

Tension: 230V

Number of phases: 1-phase

Cable length: 6.0m

Operating temperature: -30°C ... +60°C

Protection class control box: IP67

Fire protection class: UL94V0

Type 2 plug cycles: >10.000

Compatibility: Typ2, CSS2

Security: Impact and drive-over safe

Standby: 0.5W

Temperature sensor: Yes

PRODUCT DATA

Product name: Charging cable type 2 Schuko adjustable 3.7kW

Part number: 301019

Tariff number: 85371098

Scope of delivery: Charging cable, protective bag, storage strap

Packing type: Carton

VOLUMETRIC DATA

Product

Dimensions: 390x390x135mm

Weight: 3120g

Product + packaging

Dimensions: 430x400x150mm

Weight: 4030g

EAN: 4260368689958

Packaging unit

Quantity: 4

Dimensions: 610x430x415mm

Weight: 18000g

EAN: 4068697000082

